



DIAMOND PAINT MFG. CO. LTD.

TECHNICAL DATA DIAMOND SURE- RELEASE

Product Description:

Sure-Release is a blend of mineral sprits, silicones and approved surfactant that promotes clean stripping of concrete forms and form liners, to produce attractive concrete surfaces and reduce form clean-up time.

Special Features:

Sure-Release when applied correctly will not affect adhesion of Paints, Sealers, Caulkings or any coating which might be applied.

Directions for use:

Sure-Release may be applied by Spray, Roller, Brush or Rag. Best results are derived when applied as a thin film on form surfaces that are clean and dry. Do not over apply; wipe off puddles that may form with a clean rag. **Sure-Release** may be applied days, hours, or minutes before concrete is poured.

Compatibility:

Sure-Release is compatible with forms and form liners made of Steel, Plywood, Fiberglass, ABS, PVC, Urethane, Silicone, Rubber, Epoxy and Aluminum.

Coverage:

On Hard Smooth Surfaces 1500F² per gal.
On Pre-treated Plywood 1000F² per gal.
On Untreated Plywood 700F² per gal.

Properties:

Freeze Temperature	15°F
Flash Point	175°F
Viscosity	13 CPS
Density	7.37 lbs./gal.
Freeze Damage	None
V.O.C.	240 G/L

Storage:

Sure-Release may be maintained indefinitely in sealed containers at temperatures - 20°F to 140°F.

Caution:

Keep out of the reach of children.

Moderate Eye, Skin and Mucous Membrane irritant. Prolonged inhalation of concentrated vapours may cause dizziness and irritate the respiratory system.

Manufactured by: Diamond Paint Manufacturing Co. Ltd.
67 Waltham Park Road
Kingston 11
Jamaica, West Indies
e-mail: diamondpaints@cwjamaica.com

Tel.: (876) 937-495112

Fax: (876) 901-1964